

Model	Line	Standard
AUCKLAND	SKIPPER	EN ISO 20345:2011
Article	Protection	Availability in stock
90378-11	O2 FO SRC	



Preview



Sole



PU / PU ESD-plus SRC

PU-PU insole
With a new formula, we have obtained a lighter and more comfortable in-between insole. The new design of the outsole has superior performances compared with standard ones after slipping tests on wet surfaces.

Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow".

Protection Elements

Descrizione protezione



Working Environment

Special, Polivalente, Polivalente, Polivalente.

Type	Low Shoe
Upper	Dgtex. Airy, no ladder, H.T. textile Airy, no ladder, H.T. textile Airy, no ladder, H.T. textile
Lining	Breezy 3D, two-layers combination
Antislip Lining	DUALMICRO
Removable Insole	Five 4 Fit
Sole	PU / PU ESD-plus SRC
Toe Cap	
Anti-Perforation	
Size	40-48
Weight gr.	495

SRC

SRC (SRA+SRB)

Sole 94-95 PU - PU		
SRA CERAMIC	FLAT ≥ 0.32	0.41
DETERGENT SOLUTION	HEEL (width/length) ≥ 0.28	0.38
SRB STEEL	FLAT ≥ 0.18	0.26
GLYCEROL	HEEL (width/length) ≥ 0.13	0.22

Antistatic



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Symbols

